

A930RTX

ADVANCED Smart Mobile



Food & Beverage



Fashion & Retail



Transportation



Paydroid Powered
by Android 10



PCI PTS 6.x
SRED



6" HD
Display



Up to 8MP
Rear Camera



Advanced
Connectivity




















SMARTPOS

www.paxitalia.com



MAXSTORE

SPECIFICATIONS

	Operating System	Paydroid Powered by Android 10
	Processor	Cortex A55 Octa-Core, 1.6GHz + Secure Processor
	Memory	8GB eMMC Flash + 1GB DDR3 RAM Optional: 16GB eMMC Flash + 2GB DDR3 RAM Extended microSD card slot up to 128GB
	Card Readers	Chip & PIN Contactless Magnetic Stripe
	Cameras	5MP AF Rear + 0.3MP FF Front camera , with flashlight Optional: 5MP/8MP AF Rear camera Optional: 5MP/8MP AF Rear + 2MP FF Front camera
	Displays	6" IPS HD+ Multi-Point Capacitive Touch Screen
	Comms Configurations	4G/3G/2G + Wi-Fi® 2.4GHz + Bluetooth® 4.2 Optional: 4G/3G/2G + Wi-Fi® 5GHz/2.4GHz + Bluetooth® 5.0
	Battery	2600mAh 7.2V, 18.72Wh, (equal to 5200mAh/3.6V) Optional: 3350mAh 7.2V, 24.12Wh, (equal to 6700mAh/3.6V) Optional: 2000mAh 6.4V, 12.8Wh, (equal to 4000mAh/3.2V)
	Printer	80 mm/sec Paper roll outer diameter: 40mm
	SIM / PSAM	1 micro SIM + 2 PSAM Optional: 1 micro SIM + 1 Mini SIM + 1 PSAM Optional: eSIM
	Positioning	AGPS GPS GLONASS BEIDOU
	Keys / Buttons	4 Keys: Power ON/OFF Volume+ Volume- Quick Scan button
	Audio	1 Buzzer 1 Speaker 1 microphone
	Ports	1 Type C USB OTG 2 PIN POGO PIN
	Adapter	Input: 100 - 240V AC, 50Hz/60Hz Output: 5.0V DC, 2.0A
	Physical	190.36*81.2*63 mm 395g (Including battery)
	Accessories	5V/2A adapter USB Type C Charging cable Optional: Charging Base Optional: Charging + Wireless Communication Base Optional: Customized Fiscal Box
	Environmental	0°C ~ 45°C (32°F ~ 113°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 5% ~ 95% Relative Humidity, Non-Condensing
	Certifications	PCI PTS 6.x SRED EMV L1 & L2 EMV Contactless L1 Visa payWave MasterCard Contactless UPI qUICS Amex ExpressPay Discover D-PAS JCB J/Speedy Interac Flash TQM CE RoHs BQB ABECS Anatel FCC IC

