

E600Mini

ALL-IN-ONE Smart EPOS



Food & Beverage



Fashion & Retail



SMARTECR







3.5" Display



www.paxitalia.com



E600Mini Android Smart EPOS

SPECIFICATIONS

00	Operating System	Powered by PayDroid 10 + (Q10) Monitor / (Q10A) PayDroid
	Processor	Application CPU: 64 bit 8-Core Cortex A55 Quad-Core 1.6GHz Security CPU: ARM
	Memory	16GB eMMC Flash + 2GB DDR RAM Extended microSD Card Slot Up to 128GB
	Card Readers	Chip & PIN NFC Contactless Magnetic Stripe
	Display	7" IPS 600 x 1024 Pixels HD Touchscreen Optional: 7" IPS 720 x 1280 FHD Touchscreen Customer Display: 3.5" TFT 480 x 320 Pixels Touchscreen (Q10A)
©	Cameras	0.3MP, support 1D/2D code scanning Optional: 2MP Camera
((†))	Comms Configurations	4G + Wi-Fi® 2.4GHz/5GHz + Bluetooth®5.0
4	Battery	6100mAh 3.8V, 23.18 Wh
	Printer	40 lines/sec Paper Roll Outer Diameter: 50mm
SAM	SIM / SAM	2 NANO SIM
(H)	Keys / Buttons	4 Keys: Power Volume+ Volume- Quick Scan Button
⟨⟨`))	Audio	1 Speaker 1 Microphone
	Ports	1 Type-C 1 Audio Jack
-\$*	Adapter	Input: 100-240V AC, 50Hz/60Hz Output: 9V DC, 2A
	Physical	101 x 230 x 79mm, 0.54kg
Ĝ	Environmental	0°C ~ 50°C (32°F ~ 122°F) Operating Temperature, Non-Charging -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 5% ~ 96% Relative Humidity, Non-Condensing
\odot	Certifications	PCI PTS 6.x SRED EMV L1 & L2 EMV contactless L1 Visa payWave Mastercard contactless UPI qUICS American Expresspay Discover D-PAS JCB J/Speedy Interac Flash MasterCard TQM FCC UL CE RoHs Anatel









